

BOBCATRENTAL PUMP PACKAGE

TECHNICAL DATA SHEET

TECHNICAL REFERENCE SPECS

Pump Package	Bobcat
Туре	Simplex
НР	15
Voltage	480/3
FLA	18
Connection Size	2" #150 Flg
Max Flow Condition	150 GPM @ 90 PSI
Max Boost Condition	55 GPM @ 170 PSI
Max Building Size	20 Floors Of Typical Office Building with Cooling Tower Load
Dry Weight	750 Lbs.



Bobcat Rental Pump - Iso View

RENTAL PUMP PACKAGE FEATURES

- Rental Package is on a 30" X 60" X 73" cart with casters.
- Cougar Controls VFD Panel with Through the Door Disconnect and VFD Controller.
- Remote monitoring via Grundfos GRM
- Piping includes:
 - Isolation Valves
 - Check Valve
 - Gauges
 - Pressure Sensing Devices
- Grundfos CR Series vertical multi-stage pump.
- Field Install requirements (not included in Rental)
 Field Plumbing Required
 - Pipe to the suction and Discharge Connections on the package
 - no isolation or check valves required

Field Electrical Required

- Incoming 480/3 Circuit to control panel
- 50FT SO cable pre-wired to control panel
- Components on skid are pre-wired to the control panel.
- Rental includes Start Up of the system.

CLICK TO EMAIL & REQUEST RENTAL



Bobcat Rental Pump - Side View

