

OCELOT RENTAL PUMP PACKAGE

TECHNICAL DATA SHEET

TECHNICAL REFERENCE SPECS

Pump Package	Ocelot
Туре	Simplex
НР	5
Voltage	480/3
FLA	5.9
Connection Size	2.5" 150# Flg
Max Flow Condition	65 GPM @ 94 PSI
Max Boost Condition	27 GPM @ 125 PSI
Max Building Size	10 Floors Of Typical Office Building with Cooling Tower Load
Dry Weight	485 Lbs.



Ocelot Pump - Iso View

RENTAL PUMP PACKAGE FEATURES

- Rental Package is on a 30" X 60" X 73" cart with casters.
- Cougar Controls VFD Panel with Through the Door Disconnect and VFD Controller.
- Piping includes:
 - **Isolation Valves**
 - Check Valve
 - Gauges
 - **Pressure Sensing Devices**
- Grundfos CR Series vertical multi-stage pump.
- Field Install requirements (not included in Rental) Field Plumbing Required
 - Pipe to the suction and Discharge Connections on the package
 - no isolation or check valves required

Field Electrical Required

- Incoming 480/3 Circuit to control panel
- 50FT SO cable pre-wired to control panel
- Components on skid are pre-wired to the control panel.
- Rental includes Start Up of the system.





Ocelot Pump - Side View

