

## THUNDERCAT RENTAL PUMP PACKAGE

**TECHNICAL DATA SHEET** 

## **TECHNICAL REFERENCE SPECS**

Pump Package	Thundercat
Туре	Simplex
НР	40
Voltage	480/3
FLA	52
Connection Size	2.5" 250# Flg
Max Flow Condition	200 GPM @ 220 PSI
Max Boost Condition	80 GPM @ 346 PSI
Max Building Size	50 Floors Of Typical Office Building with Cooling Tower Load
Dry Weight	1050 Lbs.



- Rental Package is on a 30" X 60" X 73" H steel base. Can be picked up with pallet jack.
- Includes a Cougar Controls VFD Panel with Through the Door Disconnect and VFD Controller.
- Grundfos CR Series vertical multi-stage pump.
- Valves/Fittings Included:
  - Suction Ball Valve
  - **Discharge** check valve, ball valve, T for Gauge and transducer (can ship loose)
- Field Install requirements (not included in Rental)

Field Plumbing Required

- Pipe to the suction and Discharge Connections on the package
- no isolation or check valves required

## Field Electrical Required

- Incoming 480/3 Circuit to control panel
- components on skid are pre-wired to the control panel.
- Rental includes Start Up of the system.



Thundercat Pump - Iso View

## CLICK TO EMAIL & REQUEST RENTAL



Thundercat Pump - Side View

