

THUNDERCAT JR RENTAL PUMP PACKAGE TECHNICAL DATA SHEET

TECHNICAL REFERENCE SPECS

Pump Package	Thundercat Jr
Туре	Simplex
HP	25
Voltage	480/3
FLA	30.5
Connection Size	2.5" 250# Flg
Max Flow Condition	120 GPM @ 208 PSI
Max Boost Condition	30 GPM @ 340 PSI
Max Building Size	45 Floors Of Typical Office Building with Cooling Tower Load
Dry Weight	1050 Lbs.



Thundercat Jr Pump

CLICK TO EMAIL & REQUEST RENTAL





RENTAL PUMP PACKAGE FEATURES

- Rental Package is on a 30" X 60" X 73" H steel base. Can be picked up with pallet jack.
- Includes a Cougar Controls VFD Panel with Through the Door Disconnect and VFD Controller.
- Grundfos CR Series vertical multi-stage pump.
- Valves/Fittings Included:
 - Suction Ball Valve
 - **Discharge** check valve, ball valve, T for Gauge and transducer (can ship loose)
 - Field Install requirements (not included in Rental) Field Plumbing Required
 - Pipe to the suction and Discharge Connections on the package
 - no isolation or check valves required

Field Electrical Required

- Incoming 480/3 Circuit to control panel
- components on skid are pre-wired to the control panel.
- Rental includes Start Up of the system.